

# HIGH FLOW REGULATORS



## HF-300G/H HF-301G/H

High flow regulator with diaphragm or piston sensed options for use on liquid or gas applications.

Port size	Cv	Service	Max inlet	Seat	Max outlet	Sensing element	Venting option
1"	4.0	Gas Liquid	300bar 4350psi	PCTFE Vespe <sup>l</sup> ™	10bar 150psi	Diaphragm	Non venting
					300bar 4350psi	Piston	



## HF-250G/H HF-251G/H

High flow regulator with diaphragm or piston sensed options for use on liquid or gas applications.

Port size	Cv	Service	Max inlet	Seat	Max outlet	Sensing element	Venting option
1 1/2"	7.0	Gas Liquid	250bar 3625psi	PCTFE Vespe <sup>l</sup> ™	10bar 150psi	Diaphragm	Non venting
					250bar 3625psi	Piston	



## HF-210G/H HF-211G/H

High flow regulator with diaphragm or piston sensed options for use on liquid or gas applications. Spring / dome loaded option.

Port size	Cv	Service	Max inlet	Seat	Max outlet	Sensing element	Venting option
2"	13.0	Gas Liquid	210bar 3000psi	PCTFE Vespe <sup>l</sup> ™	10bar 150psi	Diaphragm	Non venting
					200bar 2900psi	Piston	



## HF-200G/H HF-201G/H

High flow regulator with diaphragm or piston sensed options for use on liquid or gas applications.

Port size	Cv	Service	Max inlet	Seat	Max outlet	Sensing element	Venting option
3"	30.0	Gas Liquid	200bar 2900psi	PCTFE Vespe <sup>l</sup> ™	10bar 150psi	Diaphragm	Non venting
					150bar 2175psi	Piston	